






CAP 示意图





NOTE:
1.Contact Resistance:40mOHM Max.;
2.Dielectric Withstanding Voltage:100V AC For 1 Minute;
3.Insulation Resistance:100M OHM Min.;
4.Mating And Unmating Force:
Mating Force: 5~20N
Unmating Force: 8~20N;
6~20N AFTER TEST;
5.Durability:10000 Cycles;




USB TYPE-C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A2	SSTXp1	B11	SSRXp1
A3	SSTXn1	B10	SSRXn1
A4	Vbus	B9	Vbus
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	Vbus	B4	Vbus
A10	SSRXn2	B3	SSTXn2
A11	SSRXp2	B2	SSTXp2
A12	GND	B1	GND



RECOMMEND P.C.B LAYOUT (COMPONENT SIDE)
TOLERANCE FOR PCB LAYOUT IS ± 0.05
KEEP OUT AREA



Item	Title	Material	Dispose	Q'TY
1	Shell	SUS304	Ni:30u" Min.	1PCS
2	GND Plate	SUS301		2PCS
3	Mid Plate	SUS301		1PCS
4	Contact	C7025	Mating Area: See P/N Solder Tails: Matt Tin	2PCS
5	InsertMolding	LCP E6808	UL 94V-0 Black	1PCS
6	COVER	LCP E6808	UL 94V-0 Black	1PCS

PART NO.:
SEE THE PART NUMBER CODE

深圳市纬域科技有限公司
SHENZHEN WITAREA TECHNOLOGY CO.,LTD

DRAWN BY ANDY YANG
DATE 2022.05.25

CHECKED BY JAMES XIAD
DATE 2022.05.25

APPROVED BY JASON ZENG
DATE 2022.05.25

QUALITY SYMBOL	GENERAL TOLERANCES (UNLESS SPECIFIED)
$\nabla=0$	X.XXXXX $\pm$ ---
$\nabla=0$	X.XXX $\pm$ 0.10
$\nabla=0$	X.XX $\pm$ 0.25
$\nabla=0$	X.X $\pm$ 0.30
$\nabla=0$	ANGULAR $\pm$ --°

TITLE	TYPE C 3.1/3.2 24PIN RECEPTACLE, VERTICAL-MOUNT , DUAL ROW SMT, H=15MM, L=15MM
DWG.NO.	W0026-24-VM1-S17
SHEET NO.	1 OF 1
DIMENSION STYLE	MM ONLY
DESIGN UNITS	METRIC
SCALE	1:1

THIRD ANGLE PROJECTION